



Datasheet

STAXS® Reference	Description
N-0003-L	DOTCH® Tyvek® Coat with zipper, Tyvek®, 41g/m², white, L, double bagged, 1 pc/double bag, 25 double bags/box

DOTCH[®] Tyvek[®] Coat

STAXS[®] Reference : **N-0003-SIZE**

**DOTCH[®] Tyvek[®] Coat with zipper, Tyvek[®], 41g/m², white, size, double bagged,
1 pc/double bag, 25 double bags/box**



Features & advantages

- Tyvek[®] 1422A (41g/m²)
- Very strong and resistant
- Low level of particle shedding
- Full material traceability
- Antistatic
- Verifiable quality from a guaranteed source
- Continuous bioburden testing
- Latex-free elastics
- Packed in an easy-tear HDPE cleanroom bag
- Double packed in ISO 5 cleanroom (ISO 14644-1)
- Recommended for ISO 7 cleanrooms and higher
- For single use only

Physical characteristics

Outside material	Tyvek [®] 1422A, 41g/m ²	PPE category	CE I
Colour	White	Size	S, M, L, XL, 2XL

Revision date : 09/03/2018

DOTCH[®] Tyvek[®] Coat

STAXS[®] Reference : **N-0003-SIZE**

Technical data

Attribute	Unit	N-0003-SIZE	Test Methods
Bioburden	CFU	30,63	ISO 11737-1
Particle count	number of particles/cm ²		Helmke Drum Test IEST-RP-CC003.4
≥0,3-<0,5µm		0,251	Climatic conditions: ISO 6, 18°C ± 2°C, 50% - 10% RH
≥0,5-<1µm		0,245	
≥1-<3µm		0,356	
≥3-<5µm		0,028	
≥5-<10µm		0,006	
≥10µm		0,002	
Shelf life	years	2*	

* From date of manufacture

Notes:

- Technical data shown are typical values at the time of publication
- Due to differences in test methods applied and equipment used by different manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility and under similar conditions

Revision date : 09/03/2018

DOTCH[®] Tyvek[®] Coat

STAXS[®] Reference : **N-0003-SIZE**

Packaging

Product	Ref. No.	Pieces/bag	Bags/box	Box size	Box Weight
DOTCH [®] Tyvek [®] Coat	N-0003-SIZE	1	25	40x30x24cm	5,0kg

Notes:

- Packed in HDPE cleanroom pouches with an easy-tear opening
- Box liner present in the box
- Minimum sales unit: 1 box
- Production date, lot number and expiry date can be found on the inner label and on the box

Storage

- Store in dry, clean conditions in the original packaging and keep out of direct sunlight, high temperatures and solvent vapors
- Store between 5°C and 40°C

Certification

- Antistatic treatment (EN 1149-5) – on both sides
- Produced by STAXS[®] which is certified ISO 9001:2015

Revision date : 09/03/2018

Tyvek[®] is a registered trademark of DuPont[™] or its affiliates.