



Datasheet DELTAPURE® Swab DZ-093VACTL

93 mm Polyester / Nylon Microfiber Cleanroom Swab



Product Informations

Applications

DELTAPURE® polyurethane foam and polyester swabs are designed for precision surface cleaning and application of liquid lubricants in cleanroom environments. These swabs are manufactured in ISO Class 5 cleanroom using patent processes that produce high quality swabs capable of meeting the strictest requirements of industries such as semiconductor, flat panel display, microelectronics, biotechnology and health care.

Benefits

- Absorbent and chemical resistant
- Low levels of particles and extractables
- Compatible with IPA and many cleaning solvents
- Excellent for applying lubricants and other liquids
- Suitable for cleaning sensitive surfaces

Product Specifications

Material	
Swab head	Knitted polyester / nylon microfiber
Swab handle	Polypropylene
Dimensions	
Total swab length	93 mm
Swab head	16.8 mm (L) x 6.8 mm (W) x 2.8 mm (Thickness)
Swab handle	76.2 mm (L) x 3.1 mm (Diameter)
Head shape	Flat

Order Information

Number	Product	Inner bag	Bag	Case
DZ093VACTL	DELTAPURE® Swab DZ-093VACTL		100 swabs	100 bags (10'000 swabs)



Datasheet DELTAPURE® Swab DZ-093VACTL

93 mm Polyester / Nylon Microfiber Cleanroom Swab

Technical Data		
Contamination Characteristics		
Property	Value	Test methode
Particle counts - LPC $\geq 0.5 \mu\text{m}$	2'120 counts/tip	IEST-RP-CC004.3\6.1.4
Non volatile residue (NVR) - IPA extractant	0.05 mg/tip	IEST-RP-CC004.3\7.1.2
Extractable counts (Ions) - Chloride (Cl ⁻)	< 0.05 $\mu\text{g}/\text{tip}$	IEST-RP-CC004.3\7.2.2
Extractable counts (Ions) - Sulfate (SO ₄ ²⁻)	< 0.03 $\mu\text{g}/\text{tip}$	IEST-RP-CC004.3\7.1.2
FTIR	No silicone, amide and DOP detected	
Date		
12/2019		